



Stallion 12 SC

12-Gallon Self-Contained Carpet Extractor



Where productivity is the bottom line, the Stallion 12 SC can clean quickly and efficiently. Top quality construction, remarkable ease of operation, and versatility combine for a machine that consistently outperforms the competition.

- Large wheels, adjustable handle, and lightweight construction team up for easy handling and storage.
- A low-flow switch allows water conservation (about 38 percent less water) while keeping solution flow at the same great cleaning pressure.
- Patented dual lift-off recovery buckets provide quick and convenient emptying.
- Four-wheel design for balance and reduced turning radius.
- The high speed brush motor and brush guarantee powerful agitation to release deeply embedded soil and grit, extending carpet life.
- The brush system utilizes fully sealed stainless steel ball bearings for years of trouble-free operation.
- Maintenance is a breeze—just remove two screws and open up the clamshell design body for quick internal access.



NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958
USA
www.nss.com



Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

Stallion 12 SC Specifications

Tanks -Solution Tank -Recovery Tank	12 gal (45.5 l) Dual 6 gal (45.5 l total)	Construction -Tanks -Frame -Wheels	Rotocast polyethylene Painted steel Four 8-in (20 cm) non-marking grey tread	Cord -Size -Length	12-3 SJTW safety yellow with molded plug 50 ft (15 m)
Solution Pump -Type -Watts	100 PSI bypass Diaphragm type 115(110V)-126.5(230V)	-Spray Jets -Vacuum Shoe	2 Brass 18-in (46 cm) corrosive-resistant cast aluminum	Accessory Valve	Quick-connect attachment; automatic valve actuated
Vacuum Motors -Type -Voltage	Dual, 2-stage tangential 110V-120V 220V-240V available	Brush -Type	15.25-in (39 cm) nylon bristle, Chevron design	Dimensions -Height -Length -Width	38 in (96.5 cm) 48 in (122 cm) 19 in (48 cm)
-HP -CFM	3.5 HP (2.7 kilowatts) 200	-RPM -Bearings	2,100 RPM Sealed; stainless steel	Weight -Machine -Shipping	120 lbs (54.5 kg) 136 lbs (62 kg)
Current	120V - 15 amps 240V - 8 amps	Sound Level	77 dBA @ operator	Shipping Class	125
Brush Motor -Type -Voltage	Permanent magnet 110V-120V or 220V-240V			Warranty	3 year limited 10 year poly parts
-HP -RPM	0.167 HP 2,100				

Productivity — The Stallion 12 SC will cover 1,714 sq ft per hour (coverage figures provided in the *ISSA 447 Cleaning Times*).



Patented dual lift-off recovery buckets (one shown) provide quick and convenient emptying.

1 The clearview recovery tank top allows the operator to easily see when the tanks need to be emptied.

2 The 12-gallon polyethylene tanks won't dent, crack, or corrode and are warranted for 10 years.

3 The vacuum shoe covers an 18-inch wide path.

4 Two brass spray jets provide a powerful blast of cleaning solution over the full width of the cleaning head.



5 Dual transport wheels allow easy transport and easy forward movement before each pull-back cleaning pass.

8 Convenient fingertip controls make it easy to activate the pump, vacuum motor, and brush.

7 The heavy-duty 12 ga cord, in safety yellow, provides trouble-free service, and a 50-ft reach.

6 A low-flow solution switch on the Stallion 12 SC allows the operator to use less water at the same PSI, conserving water without sacrificing cleaning power.



NSS® Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958 USA
419/531-2121 or 800/677-1663
Fax 419/531-3761
www.nss.com
mailus@nss.com
Specifications and appearance
subject to change without notice.

DISTRIBUTED BY