



Stallion 8SC

8-Gallon Self-Contained Carpet Extractor



The Stallion 8SC's maneuverability and deep-down cleaning make it the perfect extractor for restoration of small and medium-sized carpeted areas.

- The Stallion 8SC blasts solution into the carpet through its three stainless steel jets. The embedded dirt is agitated by the floating brush, which automatically adjusts to different carpet pile heights. The solution and loosened soil are then extracted through a cast aluminum 16-inch shoe by the powerful 1.88 HP vacuum motor.
- 8-gallon solution and recovery tanks minimize the time spent emptying and refilling tanks, increasing productivity.
- The hinged, rotocast polyethylene body provides easy access to internal components, simplifying maintenance.
- The Stallion 8SC has an accessory connector for use with optional stair and upholstery cleaning tools.
- Ideal for offices, hotel rooms, and other areas where carpet restoration is required the Stallion 8SC is a workhorse built for the rigors of heavy-duty commercial use.



NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958
USA
www.nss.com

Stallion 8SC Specifications

Tanks -Solution Tank -Recovery Tank	8 gal. (30 l.) 8 gal. (30 l.)	Construction -Tanks -Frame -Wheels	Rotocast polyethylene Powder-coated steel Two 10-in. (25 cm) non-marking grey tread	Cord -Size	14-3 SJT safety yellow twist-lock detachable plug
Solution Pump -Type -Watts	100 PSI bypass Diaphragm type 115(110V.)-126.5(230V.)	-Spray Jets	3 stainless steel, ¼ turn snap in or out	-Length	50 ft. (15 m)
Vacuum Motor -Type -Voltage	3-stage tangential 110V.-120V. 220V.-240V. available	-Vacuum Shoe	16-in. (41 cm) corrosive-resistant cast aluminum	Accessory Valve	Quick-connect attachment; automatic valve actuated
-HP -Closed Waterlift	1.88 HP (1400 watts) 117 in. (297 cm)	Brush -Type	14.75-in. (37.5 cm) nylon bristle, ABS plastic core	Float Shut-Off	Ball type
Current	120V. - 12 amps 240V. - 6.2 amps	-RPM -Bearings	1,200 RPM Sealed; protected with additional string guard	Dimensions -Height -Length -Width	34 in. (86 cm) 35 in. (90 cm) 16 in. (41 cm)
Brush Motor -Type -Voltage	Permanent magnet 110V.-120V. or 220V.-240V.	Sound Level	77 dbA @ operator	Weight -Machine -Shipping	84 lbs. (38 kg) 100 lbs. (45 kg)
-HP -RPM	.125 HP 1,200			Shipping Class	125
				Warranty	3 year limited 10 year poly parts

Productivity — The Stallion 8SC will cover 1,400 sq. ft. per hour.



Access to internal components is as easy as removing two bolts and lifting up the body.



An optional 3-jet wand kit (4892869 — sold separately) can be used to clean carpeted stairs and other hard-to-reach areas.

1 A foam-sensitive ball-type float protects the vacuum motor from damage.

2 The 8-gallon polyethylene tanks won't dent, crack, or corrode and are warranted for 10 years.

3 The vacuum shoe covers a 16-inch wide path.


4 Three stainless-steel spray jets snap in and snap out for trouble-free maintenance.

8 Convenient fingertip controls make it easy to activate the pump, vacuum motor, and brush.

7 The twist-lock connector prevents the cord from accidentally being pulled out.

6 The accessory connector lets you use optional extraction tools with the Stallion 8SC.

5 The floating brush adjusts to different carpet pile heights. Stainless-steel string guard protects the brush bearings.



NSS® Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958 USA
419/531-2121 or 800/677-1663
Fax 419/531-3761
www.nss.com
mailto:mailus@nss.com
Specifications and appearance
subject to change without notice.

DISTRIBUTED BY

Printed in USA

©2006 NSS Enterprises, Inc.

#9094801 REV C 8/06